

WALL



OVERVIEW

The TFA Wall, chambered in 5.56 NATO OR .300 Blackout (SPECIAL ORDER ONLY), is inspired by the Walls of Troy, which served as the city's primary defense. As these walls were virtually indestructible surviving a 10-year siege, the TFA Wall mimics the same primary defense and reliability. The WALL is the perfect entry level rifle for anyone wanting an upgraded AR. Equipped with the TFA fully adjustable (3-6lb) single stage drop in trigger, black nitride BC5 NiB bolt, 7075 billet aluminum upper/lower receiver and TFA M-LOK rail set, fixed .750 DI gas block, 4150 chrome moly barrel 1:7 twist, mid-length gas system, magpul CTR stock and 30 round Magpul Pmag.

FEATURES

Magpul CTR carbine stock.

M-LOK GEN II hand guard system.

Gen III ambi charging handle.

CNC machined, 7075-T6 aircraft billet aluminum [lower, upper].

Flash Suppressor.

Enhanced flared lower magwell.

TFA fully adjustable (3-6lb) single stage drop in trigger [Available in straight or curved configuration].

Tension set screw with matching lock screw to maintain tightness of upper and lower match set.

Nitrided mil-spec BCG with a Nickle Boron coated bolt assembly.

4150 Chromemoly polygonal rifling barrel chambered in 5.56 NATO 1:7 twist.

Mid-Length gas system.

Proprietary low profile gas block.

SPECS

Barrel Length	16 in [406mm]
Magazine Included	Yes
Magazine Type	[1] 30rd Polymer Mag
Action Type	Semi-Auto
Barrel Material	Chromoly Steel
Trigger	Drop-In Adjustable
Collapsed Length	26.5 in [673mm]
Trigger Weight	3.0 to 6.0 lbs
Forend Type	6061-T6 Billet 15 in length
Grip Type	Polymer
Receiver Finish	Cerakote
Overall Length	37.0 in [939.8mm]
Overall Width	1.75 in [44.45mm]
Overall Height	70 in [1778mm]
Overall Weight	6.57 lbs [2.98 kg]
Accessory Rail	M-LOK
Operating System	Direct Impingement

CONFIG. 1

Caliber	5.56 NATO
Twist Ratio	1-7 twist
Barrel Threads	1/2 in - 28 tpi

CONFIG. 2 (SPECIAL ORDER ONLY)

Caliber	300 BLK
Twist Ratio	1-7 twist
Barrel Threads	5/8 in - 24 tpi